



DryAIR 250

DryAIR

*The Solution to Your Portable
Compressor Moisture Problems*

DryAIR works by effectively removing harmful moisture from the discharge air of portable gas & diesel compressors. Cools air to within 15° of ambient temperature.

DryAIR units deliver cleaner compressed air, resulting in virtually no contamination on blast surfaces. Primer and paint adhere better, without *fish-eye* and troublesome spotting on finish coats.

Moisture is a poor lubricant and causes premature failure of paving breakers, jackhammers, rivet busters and related air tools. DryAIR will make a significant difference in prolonging the life of your tools.



DryAIR 250TM

Tongue-Mount units are easy to install and make a valuable addition to Doosan / IR portable compressors. They can easily be retrofitted to mount on various other brands as well.

PERFORMANCE

MAXIMUM FLOW
250 CFM

MAXIMUM OPERATING PRESSURE
200 psig

MAXIMUM PRESSURE DROP
5 psig

FAN POWER REQUIREMENT
17.5 amps, 12 volts DC

DIMENSIONS
30" W x 14" D x 30" H

WEIGHT
50 lbs

DryAIR 250FS CLASSIC

Free-Standing self-contained units are mounted in a rugged box frame designed to withstand the rigorous demands of the construction industry. They can be used on any gas or diesel portable compressor.

PERFORMANCE

MAXIMUM FLOW
250 CFM

MAXIMUM OPERATING PRESSURE
200 psig

MAXIMUM PRESSURE DROP
5 psig

FAN POWER REQUIREMENT
17.5 amps, 12 volts DC

DIMENSIONS
24" W x 19" D x 32" H

WEIGHT
70 lbs

DryAIR 250FS GEN II

Free-Standing space-saving design with a 17" depth to fit under pickup truck bed rail height. They can be used on any gas or diesel portable compressor.

PERFORMANCE

MAXIMUM FLOW
250 CFM

MAXIMUM OPERATING PRESSURE
200 psig

MAXIMUM PRESSURE DROP
5 psig

FAN POWER REQUIREMENT
17.5 amps, 12 volts DC

DIMENSIONS
24" W x 17" D x 26" H

WEIGHT
52 lbs