

FITTING INSTALLATION GUIDE FOR CONE BOTTOM TANKS

Norwesco cone bottom tanks come standard with a bulkhead fitting installed or the tank may be ordered without a fitting. For instances when you would like to install a smaller or larger bulkhead fitting, would like to install a bolted fitting or would like to install additional fittings, please refer to this guide.

The maximum fitting sizes shown for cone bottom tanks are based on installing the fitting in the standard flat area in the bottom cone of the tank. All cone bottom stands will accommodate maximum fitting sizes. Please contact a Norwesco distributor or Norwesco Customer Service if you would like to install a fitting in any other location.

| Gallon Capacity | Slope | Maximum Bulkhead Fitting Size | Maximum Bolted Fitting Size |
|-----------------|-------|-------------------------------|-----------------------------|
| 125 | 15° | 2" | 2" |
| 160 | 45° | 2" | 2" |
| 175 | 30° | 2" | 2" |
| 300 | 45° | 3" | 3" |
| 300 | 30° | 3" | 3" |
| 310 | 30° | 2" | 2" |
| 500 | 45° | 3" | 3" |
| 500 | 30° | 3" | 3" |
| 550 | 20° | 3" | 3" |
| 750 | 20° | 3" | 3" |
| 1000 | 45° | 3" | 3" |
| 1020 | 15° | 3" | 3" |
| 1050 | 20° | 3" | 3" |
| 1320 | 15° | 3" | 3" |
| 1500 | 45° | 3" | 3" |
| 1600 | 30° | 3" | 3" |
| 1720 | 15° | 3" | 3" |
| 2500 | 30° | 3" | 3" |
| 2500 | 15° | 3" | 3" |
| 3000 | 30° | 3" | 3" |
| 3000 | 15° | 3" | 3" |
| 4950 | 15° | 3" | 3" |
| 5500 | 30° | 4" | 4" |
| 6000 | 10° | 4" | 4" |
| 6000 | 15° | 4" | 4" |
| 7500 | 30° | 4" | 4" |
| 10000 | 15° | 4" | 4" |
| 10000 | 30° | 4" | 4" |

3/18/19