

Gallon Capacity	Slope	Diameter	Overall Height
55	15°	23"	39"
100	15°	23"	63"
125 w/stand	15°	48"	41"/12" †
150	15°	36"	43"
160	45°	36"	52"
175 w/stand	30°	43"	49"/9" †
200	15°	36"	55"
250	15°	36"	67"
300 w/stand	30°	49"	61"/9" †
300	15°	36"	80"
300	45°	48"	56"
310 w/stand	30°	43"	72"/9" †
350	45°	52"	58"
500 w/stand	30°	49"	87"/9" †
500	45°	52"	82"
500	45°	48"	85"
550	20°	72"	47"
550 w/stand	20°	73"	57"/11" †
750	20°	72"	56"
750 w/stand	20°	73"	67"/11" †
750	45°	52"	105"
1000	45°	72"	89"
1020	15°	91"	53"
1050	20°	72"	75"
1050 w/stand	20°	73"	86"/11" †
1320	15°	91"	64"
1500	45°	72"	118"
1600	30°	88"	84"
1600 w/stand	30°	89"	96"/11" †
1720	15°	91"	78"
2500	15°	91"	108"
2500	30°	96"	105"
2500 w/stand	30°	99"	116"/10" †
3000	15°	91"	120"
3000	30°	96"	123"
3000 w/stand	30°	99"	134"/10" †
4950	15°	102"	159"
5500	30°	119"	148"
6000	10°	102"	189"
6000	15°	102"	195"
7500	30°	141"	149"
10,000	15°	142"	173"
10,000	30°	141"	190"

† Distance from bottom of cone to ground